Setup Kits

TRICO

Protect Your Equipment

Pressure differential between the equipment housing and surrounding atmosphere is a leading cause of moisture ingression. Equipment operation where housing temperature fluctuations occur during frequent on/off running conditions, process fluid temperature changes, outdoor use, and air flow over the equipment create a "breathing" condition as pressure is equalized.

This "breathing" condition allows moisture to be introduced into the equipment causing the oil to absorb it at a variable rate depending on temperature, oil type, and lubricant agitation. The Setup Kits are used to minimize the detrimental effects of the equipment "breathing".

Protect the integrity of your in-service lubricants with the Setup Kits.





Benefits:

- Extended equipment life
- Increased lubricant life
- Extended oil change intervals
- Decreased equipment maintenance
- Increased savings in maintenance costs

Includes Watchdog EX Desiccant Breather:

The Watchdog EX Breather is the perfect solution for extreme operating environments that include high humidity and dust. They incorporate two check valves, one to control airflow into the protected reservoir and one to control airflow out. This prolongs the life of the desiccant by allowing the air to flow through the breather only when needed to protect the integrity of the equipment.




Selection Chart:

Setup Kit includes the following items:

- Closed System Oiler with Wire Guard
- EX Desiccant Breather 1/2" FNPT (39110)
- 316 Stainless Steel Fittings
- Stainless Braided Flex Line

Model No.	Description
40407	Setup Kit - 4 oz Closed System, EX Breather, and Braided Line
40408	Setup Kit - 8 oz Closed System, EX Breather, and Braided Line
40409	Setup Kit - 16 oz Closed System, EX Breather, and Braided Line





Selection Chart:

Setup Kit includes the following items:

- Closed System Oiler with Wire Guard
- EX Desiccant Breather 1/2" FNPT (39110)
- 316 Stainless Steel Fittings
- 316 Stainless Steel Tube

Model No.	Description
40404	Setup Kit - 4 oz Closed System, EX Breather, and 316 SS Tube
40405	Setup Kit - 8 oz Closed System, EX Breather, and 316 SS Tube
40406	Setup Kit - 16 oz Closed System, EX Breather, and 316 SS Tube

Selection Chart:

To create a Setup Kit with the Watchdog Oiler:

- Select appropriate Watchdog Oiler
- Order Watchdog Oiler, 316 SS Nipple, and EX Desiccant Breather Separately

Model No.	Description
31833	316 SS Watchdog Oiler with 1" NPT and Wire Guard
31836	316 SS Watchdog Oiler with 3/4" NPT and Wire Guard
31840	316 SS Watchdog Oiler with 1/2" NPT and Wire Guard
10488	1/2" x 1-1/2" Nipple 316 SS
39110	EX Desiccant Breather 1/2" FNPT

