

## VERTICAL FEED PUMP WITH ELECTRO-MECHANICAL DRIVE

**NEW!**  
Explosion  
Proof

- Refillable
- Immediate Start/Stop
- Variable Dispensing Rates
- Auto Locking Mode
- Low Battery Sensing
- Daily Dispensing Rate Display
- UL Explosion Proof

Introducing a **NEW** member to Trico's Streamliner Grease Dispenser Family...

Streamliner M-UL is a single point grease lubricator rated to be used in most hazardous locations. The unit is designed for applications where it is essential to have precise amount of grease delivered to critical machine components. The Streamliner M-UL unit provides variable feed rates lasting from half to twelve months. It includes a powerful positive displacement pump designed to provide precise metering of lubricant in remote areas up to ten feet.

The grease is supplied in 125cc or 250cc grease pouches. Grease pouches and battery pack are replaceable as a "Service Pack". The service pack consists of one of six standard greases.

### HAZARDOUS AREA

The Streamliner M-UL is UL approved to meet the following requirements:

UL79, Power-Operated pumps for Petroleum dispensing products, Eighth Edition ANSI/ISA-12.12.01-2000, Nonincendive Electrical equipment for use in Class I and II, Division 2 and Class III, Divisions 1 and 2 Hazardous locations.

HAZARDOUS AREA	
RATING	DESCRIPTION
Class I	Flammable Gases, Vapors or Liquids
Division 2	Where ignitable concentrations of flammable gases, vapors and liquids are not likely to exist under normal operating conditions.
Groups - C & D	C (Ethylene), D (Propane)



### SPECIFICATIONS

Grease Capacity*	125 cc (4 oz) or 250 cc (8 oz)
Power Supply*	DC 4.5 Volt (Replaceable)
Operating Pressure	200 psi
Unit Operating Temperature	14°F - 122°F
Dispensing Rates	Half, 1, 2, 4, 6, 12 months

\*Grease pouch and power supply are replaceable in one package (Service Pack)

### PART NUMBERS

MODEL	Capacity	NPT	Units/Case
33371	250 cc	3/8	8
33372	125 cc	3/8	8

\*Grease pouch and power supply are sold separately as Service Pack

### SERVICE PACK PART NUMBERS

MODEL	Capacity	Grease Type	Units/Case
33349	125 cc	Mobilith XHP 222	20
33350	125 cc	Exxon Unirex EP2	20
33351	125 cc	Exxon Unirex N2	20
33352	125 cc	Mobil FM 222	20
33353	125 cc	Mobilith SHC 220	20
33354	125 cc	Mobilith SHC PM 460	20

MODEL	Capacity	Grease Type	Units/Case
33356	250 cc	Mobilith XHP 222	20
33357	250 cc	Exxon Unirex EP2	20
33358	250 cc	Exxon Unirex N2	20
33359	250 cc	Mobil FM 222	20
33360	250 cc	Mobilith SHC 220	20
33361	250 cc	Mobilith SHC PM 460	20

